



SSCE12V12L1

SSCE12V12L1

Bi-directional 12V Low Capacitance ESD Protector


● Description

The SSCE12V12L1 protects sensitive semiconductor components from damage or upset due to electrostatic discharge (ESD) and other voltage induced transient events. They feature large cross-sectional area junctions for conducting high transient currents, offer desirable electrical characteristics for board level protection, such as fast response time, low operating voltage. It gives designer the flexibility to protect one unidirectional line in applications where arrays are not practical.

● Feature

- ◇ DFN0603-2L package
- ◇ Replacement for MLV(0201)
- ◇ Bidirectional configurations
- ◇ Response time is typically < 1 ns
- ◇ Low clamping voltage
- ◇ RoHS compliant
- ◇ Transient protection for data lines to
IEC 61000-4-2(ESD) ± 30 KV(air), ± 30 KV(contact);
IEC 61000-4-4 (EFT) 40A (5/50ns)

● PIN configuration



● Applications

- ◇ Cellular phones
- ◇ Portable devices
- ◇ Digital cameras
- ◇ Power supplies

● Mechanical data


- ◇ Lead finish: 100% matte Sn(Tin)
- ◇ Mounting position: Any
- ◇ Qualified max reflow temperature: 260°C
- ◇ Device meets MSL 1 requirements
- ◇ Pure tin plating: 7 ~ 17 μ m
- ◇ Pin flatness: ≤ 3 mil



SSCE12V12L1

● Electronic Parameter

Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
P_{PP}	Peak Pulse Power
C_J	Junction Capacitance
I_F	Forward Current
V_F	Forward Voltage @ I_F



● Absolute maximum rating @TA=25°C

Symbol	Parameter	Value	Units
P_{PP}	Peak Pulse Power (8/20 μ S)	30	W
I_{PP}	Peak Pulse Current (8/20 μ S)	3	A
T_{STG}	Storage Temperature	-55/+150	°C
T_J	Operating Temperature	-55/+150	°C





● Electrical Characteristics @TA=25°C

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Peak Reverse Working Voltage	V_{RWM}				12	V
Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$		15		V
Reverse Leakage Current	I_R	$V_{RWM} = 12\text{V}, T = 25^\circ\text{C}$			1	μA
Clamping Voltage	V_C	$I_{PP} = 2\text{A}, T_p = 8/20\mu\text{s}$		16	18	V
Junction Capacitance	C_J	$V_R = 0\text{V}, f = 1\text{MHz}$		10	15	pF



SSCE12V12L1

- **Typical Performance Characteristics**





SSCE12V12L1




Fig 5. TLP Measurement




Fig 6. Capacitance vs. Reverse voltage




Fig 7. ESD clamping voltage (IEC61000-4-2 +8KV contact)




Fig 8. ESD clamping voltage (IEC61000-4-2-8KV contact)



SSCE12V12L1





Fig 9. Typical Leakage Current vs. Temperature

- **Solder Reflow Recommendation**

Peak Temp=257°C, Ramp Rate=0.802deg. °C/sec





SSCE12V12L1

- **Package Information**


Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCE12V12L1	DFN0603-2L(Pb-Free)	10000/Tape&Reel	7"

Mechanical Data


Case:DFN0603-2L

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters		
	Min	Typ	Max
A	0.270	0.300	0.340
B	0.200	0.250	0.300
D	0.550	0.600	0.650
E	0.250	0.300	0.350
e	-	0.350	-
F1	0.130	0.180	0.230
F2	0.130	0.180	0.230
L1	0.015	0.030	0.045
L2	0.015	0.030	0.045
H1	0.030	0.045	0.060
H2	0.030	0.045	0.060

Recommended Pad outline



Suggested PCB Layout



SSCE12V12L1

DISCLAIMER

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.