



SSCE5V022D3


SSCE5V022D3

Ultra-low Capacitance Bidirectional Micro Packaged TVS Diodes for ESD Protection

● Description

The SSCE5V022D3 is designed to protect voltage sensitive components from ESD and transient voltage events. Excellent clamping capability, low leakage, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium.

● PIN configuration



SOD-523

● Applications

- Cellular phones
- Portable devices
- Digital cameras
- Power supplies

● Features

- Small Body Outline Dimensions
- Low Body Height
- Peak Power up to 45Watts @ 8x20_s Pulse
- Low Leakage current
- Response Time is Typically < 1 ns
- IEC61000-4-2(ESD)±25kV(air),±25kV(contact)
- IEC61000-4-2 Level 4 ESD Protection

ORDERING INFORMATION

Device	Qty per Reel	Reel Size
SSCE5V022D3	3000	7Inch


Maximum ratings (Temp=25°C Unless Otherwise Specified)			
Parameter	Symbol	Value	Unit
Peak Pulse Power (tp=8/20μs waveform)	P _{PPP}	45	Watts
Peak Pulse Current(tp=8/20μs waveform)	I _{PP}	4	A
ESD Rating per IEC61000-4-2:	Contact	30	KV
	Air	30	
Lead Soldering Temperature	T _L	260 (10 sec.)	°C
Operating Temperature Range	T _J	-55 ~ 150	°C
Storage Temperature Range	T _{STG}	-55 ~ 150	°C



SSCE5V022D3

Electrical characteristics (T _{amb} =25°C Unless Otherwise Specified)								
Device	V _{RWM}	I _R @ V _{RWM}	Marking	V _{BR} @ 1 mA	V _C	I _{pp}	C	
	(V)	(uA)		Min	@ I _{pp} =4A	Max	Typ	Ma x
				(Volts)	Type(V)	(A)	(pF)	(pF)
SSCE5V022D3	5.0	1.0	2B	6.0	11.6V	4	9	15


Symbol	Parameter
V _{RWM}	Working Peak Reverse Voltage
V _{BR}	Breakdown Voltage @ I _T
V _C	Clamping Voltage @ I _{pp}
I _T	Test Current
I _{RM}	Leakage current at V _{RWM}
I _{pp}	Peak pulse current
C _O	Off-state Capacitance
C _J	Junction Capacitance






SSCE5V022D3


Typical electrical characterist applications



Pulse Waveform



Non-Repetitive Peak Pulse Power vs. Pulse Time



Power Derating Curve

Application Note

Electrostatic discharge (ESD) is a major cause of failure in electronic systems. Transient Voltage Suppressors (TVS) are an ideal choice for ESD protection. They are capable of clamping the incoming transient to a low enough level such that damage to the protected semiconductor is prevented.

Surface mount TVS offers the best choice for minimal lead inductance. They serve as parallel protection elements, connected between the signal lines to ground. As the transient rises above the operating voltage of the device, the TVS becomes a low impedance path diverting the transient current to ground. The BVSEHD3125V0 is the ideal board level protection of ESD sensitive semiconductor components.

The tiny SOD-523 package allows design flexibility in the design of high density boards where the space saving is at a premium. This enables to shorten the routing and contributes to hardening against ESD.





SSCE5V022D3

Mechanical Data


Case:SOD-523

Case Material: Molded Plastic. UL Flammability



Dim [⊃]	Millimeters [⊃]	
	Min [⊃]	Max [⊃]
A [⊃]	1.10 [⊃]	1.30 [⊃]
B [⊃]	0.75 [⊃]	0.85 [⊃]
C [⊃]	0.50 [⊃]	0.70 [⊃]
D [⊃]	0.25 [⊃]	0.35 [⊃]
J [⊃]	0.08 [⊃]	0.15 [⊃]
K [⊃]	0.15 [⊃]	0.25 [⊃]
S [⊃]	1.50 [⊃]	1.70 [⊃]

Recommended Pad outline





SSCE5V022D3

DISCLAIMER

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.