



SSCE7V012L1

SSCE7V012L1

Bi-directional 7V Normal Capacitance ESD Protector

● Description

The SSCE7V012L1 protects sensitive semiconductor components from damage or upset due to electrostatic discharge (ESD) and other voltage induced transient events. They feature large cross-sectional area junctions for conducting high transient currents, offer desirable electrical characteristics for board level protection, such as fast response time, low operating voltage. It gives designer the flexibility to protect one unidirectional line in applications where arrays are not practical.


● Feature

- ◊ DFN0603-2L package
- ◊ Replacement for MLV(0201)
- ◊ Bidirectional configurations
- ◊ Response time is typically < 1 ns
- ◊ Low clamping voltage
- ◊ RoHS compliant
- ◊ Transient protection for data lines to IEC 61000-4-2(ESD)
 $\pm 20\text{KV}(\text{air}), \pm 20\text{KV}(\text{contact})$; IEC 61000-4-4 (EFT)
40A (5/50ns)

● Electronic Parameter

Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
P_{PP}	Peak Pulse Power
C_J	Junction Capacitance
I_F	Forward Current
V_F	Forward Voltage @ I_F

● PIN configuration




● Applications

- ◊ Cellular phones
- ◊ Portable devices
- ◊ Digital cameras
- ◊ Power supplies

● Mechanical data

- ◊ Lead finish:100% matte Sn(Tin)
- ◊ Mounting position: Any
- ◊ Qualified max reflow temperature:260 °C
- ◊ Device meets MSL 1 requirements
- ◊ Pure tin plating: 7 ~ 17 um
- ◊ Pin flatness: $\leq 3\text{mil}$



- **Absolute maximum rating @TA=25°C**

Symbol	Parameter	Value	Units
P _{PP}	Peak Pulse Power (8/20μS)	30	W
I _{PP}	Peak Pulse Current (8/20μS)	6	A
T _{STG}	Storage Temperature	-55/+150	°C
T _J	Operating Temperature	-55/+150	°C

- **Electrical Characteristics @TA=25°C**

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Peak Reverse Working Voltage	V _{RWM}				7.0	V
Breakdown Voltage	V _{BR}	I _t = 1mA	7.5			V
Reverse Leakage Current	I _R	VRWM = 7.0V, T=25°C			1.0	μA
Clamping Voltage	V _C	IPP = 2A, T _P = 8/20μs		13.0	15.0	V
Junction Capacitance	C _J	VR=0V, f = 1MHz		13.0	15.0	pF

- **Typical Performance Characteristics**




Fig 1.Pulse Waveform




Fig 2.Power Derating Curve




Fig 3. Clamping voltage vs. Peak pulse current




Fig 4. Non-Repetitive Peak Pulse vs. Pulse time




Fig 5. TLP Measurement




Fig 6. Capacitance vs. Reverses voltage




Fig 7.Typical Leakage Current vs. Temperature




Fig 8. ESD clamping voltage

(IEC61000-4-2 +8KV contact)





Fig 9. ESD clamping voltage
(IEC61000-4-2-8KV contact)

- Solder Reflow Recommendation

Peak Temp=257°C, Ramp Rate=0.802deg. °C/sec



- Package Information


Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCE7V012L1	DFN0603-2L(Pb-Free)	10000/Tape&Reel	7"

Mechanical Data


Case: DFN0603-2L

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters		
	Min	Typ	Max
A	0.270	0.300	0.340
B	0.200	0.250	0.300
D	0.550	0.600	0.650
E	0.250	0.300	0.350
e	-	0.350	-
F1	0.130	0.180	0.230
F2	0.130	0.180	0.230
L1	0.015	0.030	0.045
L2	0.015	0.030	0.045
H1	0.030	0.045	0.060
H2	0.030	0.045	0.060

Recommended Pad outline



Suggested PCB Layout



SSCE7V012L1

DISCLAIMER

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.