



# SSCTXXX12D1

## SSCTXXX12D1 Series

Small Surface Mount TVS Diode for ESD Protection

### ● Description

The SSCTXXX12D1 is low capacitance transient voltage suppressor array for high speed data interface that designed to protect sensitive electronics from damage or latch-up due to ESD lightning, and other voltage induced transient events. All pins are rated to withstand 15kV ESD pulses using the IEC 61000-4-2 air discharge method, which can meet the requirement of level 4.


### ● Feature

- ◇ 3000W~6000W peak pulse power ( $t_P = 8/20\mu s$ )
- ◇ SOD-123FL Package
- ◇ Working voltage: 7V, 12V, 24V
- ◇ Low clamping voltage
- ◇ Low capacitance
- ◇ RoHS compliant transient protection for high speed data lines to IEC61000-4-2(ESD)  $\pm 15kV$ (air),  $\pm 8kV$ (contact)

### ● Electronic Parameter

Symbol	Parameter
$V_{RWM}$	Peak Reverse Working Voltage
$I_R$	Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Breakdown Voltage @ $I_T$
$I_T$	Test Current
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage @ $I_{PP}$
$P_{PP}$	Peak Pulse Power
C	Junction Capacitance

### ● PIN configuration




Topview

### ● Applications

- ◇ USB 2.0 Power & Data Line Protection
- ◇ DVI & HDMI Port Protection
- ◇ Serial ATA Port Protection
- ◇ Mobile Handsets
- ◇ Digital Cameras and camcorders
- ◇ PDA & MP3 Players
- ◇ Digital TV and Set-top Boxes

### ● Mechanical data

- ◇ Lead finish: 100% matte Sn(Tin)
- ◇ Mounting position: Any
- ◇ Qualified max reflow temperature: 260 °C
- ◇ Device meets MSL 1 requirements
- ◇ Pure tin plating: 7 ~ 17 um





# SSCTXXX12D1

- Absolute maximum rating @TA=25°C

Symbol	Parameter	Value	Units
P <sub>PP</sub>	Peak Pulse Power (8/20μS)	3000~6000	W
T <sub>STG</sub>	Storage Temperature	-55/+150	°C
T <sub>J</sub>	Operating Temperature	-55/+150	°C

- Electrical Characteristics @TA=25°C

Electrical characteristics ( T <sub>amb</sub> =25°C Unless Otherwise Specified)									
Device*	V <sub>RWM</sub>	V <sub>BR</sub> @ I <sub>T</sub> (V)		I <sub>T</sub>	I <sub>R</sub> @ V <sub>RWM</sub>	V <sub>C</sub> (Max)	I <sub>PP</sub> (Max)	Capacitance (Typ)	P <sub>ppp</sub> (tp=8/20μs waveform)
	(V)	Min	Max	(mA)	(μA)	(V)	(A)	(nF)	Watts
SSCT7V012D1	7.0	8.0	10	1	5	16	200	0.8	3000
SSCT12V12D1	12	13.3	15	1	5	30	200	0.5	4500
SSCT24V12D1	24	26.5	30	1	5	31	200	0.3	6000

- Typical Performance Characteristics




Fig 1. Pulse Waveform





Fig 2. Power Derating Curve




# SSCTXX12D1



Non-Repetitive Peak Pulse Power vs. Pulse Time

## ● Solder Reflow Recommendation

Peak Temp=257°C, Ramp Rate=0.802deg. °C/sec





# SSCTXXX12D1

- **Package Information**




## Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCTXXX12D1	SOD-123FL	3000	7 Inch

## Mechanical Data


Case:SOD-123F

Case Material: Molded Plastic. UL Flammability



Dim	Millimeters	
	Min	Max
A	2.50	2.90
B	1.50	1.90
C	0.095	1.20
D	0.70	1.20
E	0.35	0.85
H	0	0.1
K	3.40	3.90

## Recommended Pad outline





# SSCTXXX12D1

---

## DISCLAIMER

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE ) AND THEREFORE OUTSIDE THE WARRANTED RANGE.