



## SSCE3V312L1

Ultra-low Capacitance Bidirectional Micro Packaged TVS Diodes for ESD Protection

### ● Description


The SSCE3V312L1 is designed with SSC process TVS technology to protect voltage sensitive components from ESD. Excellent clamping capability, low leakage, and fast response time provide best in class protection on designs that are exposed to ESD. Because of its small size, it is suited for use in cellular phones, MP3 players, digital cameras and many other portable applications where board space comes at a premium. Also because of its low capacitance, it is suited for use in high frequency designs such as USB 2.0 high speed, USB 3.0 super speed, USB 3.1 super speed ,VGA, DVI, HDMI, eSATA and other high speed line applications.

It has been specifically designed to protect sensitive components which are connected to data and transmission lines from overvoltage caused by ESD(electrostatic discharge), and EFT (electrical fast transients).

### ● Feature

- ✧ 80W peak pulse power ( $t_p = 8/20\mu s$ )
- ✧ DFN0603-2L Package
- ✧ Working voltage: 3.3V
- ✧ Low clamping voltage
- ✧ Low capacitance
- ✧ Low leakage current
- ✧ Complies with following standards:
  - IEC 61000-4-2 (ESD) immunity test
    - Air discharge:  $\pm 25kV$
    - Contact discharge:  $\pm 20kV$
  - IEC61000-4-5 (Lightning) 5A (8/20 $\mu s$ )
- ✧ RoHS Compliant

### ● PIN configuration



Top view



Marking

### ● Applications

- ✧ DVI & HDMI Port Protection
- ✧ USB 2.0 and USB 3.0
- ✧ SATA and eSATA
- ✧ Serial and Parallel Ports
- ✧ Projection TV
- ✧ Notebooks, Desktops, Servers


### ● Mechanical data

- ✧ Lead finish:100% matte Sn(Tin)
- ✧ Mounting position: Any
- ✧ Qualified max reflow temperature:260°C
- ✧ Device meets MSL 3 requirements
- ✧ Pure tin plating: 7 ~ 17  $\mu m$
- ✧ Pin flatness: $\leq 3mil$



## ● Electronic Parameter

Symbol	Parameter
$V_{RWM}$	Peak Reverse Working Voltage
$I_R$	Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Breakdown Voltage @ $I_T$
$I_T$	Test Current
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage @ $I_{PP}$
$P_{PP}$	Peak Pulse Power
$C_J$	Junction Capacitance



## ● Absolute maximum rating @ $T_A=25^{\circ}C$


Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 $\mu$ s)	$P_{PP}$	80	W
Peak Pulse Current (8/20 $\mu$ s)	$I_{PP}$	5	A
ESD Rating per IEC61000-4-2:	Contact	20	KV
	Air	25	
Storage Temperature	$T_{STG}$	-55/+150	$^{\circ}C$
Operating Temperature	$T_J$	-55/+125	$^{\circ}C$

## ● Electrical Characteristics @ $T_A=25^{\circ}C$


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Working Voltage	$V_{RWM}$				3.3	V
Breakdown Voltage	$V_{BR}$	$I_T = 1mA$	4.8			V
Reverse Leakage Current	$I_R$	$V_{RWM} = 3.3V$			0.2	$\mu A$
Clamping Voltage	$V_C$	$I_{PP} = 1A, t_P = 8/20\mu s$		9		V
Clamping Voltage	$V_C$	$I_{PP} = 5A, t_P = 8/20\mu s$		13	16	V
Junction Capacitance	$C_J$	$V_R = 0V, f = 1MHz$		0.3		pF




## ● Typical Performance Characteristics




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time



Clamping Voltage vs. Peak Pulse Current



Power derating vs. Ambient temperature



8/20 $\mu$ s Pulse Waveform



- **Package Information**


### Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCE3V312L1	DFN0603-2L	15000	7 Inch

### Mechanical Data


Case:DFN0603-2L

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters	
	Min	Max
A	0.230	0.330
A1	0.000	0.050
A3	0.102REF	
D	0.550	0.650
E	0.250	0.350
b	0.215	0.275
L	0.12	0.23
L1	0.12	0.23
e	0.40BSC	

### Recommended Pad outline





## DISCLAIMER

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE ) AND THEREFORE OUTSIDE THE WARRANTED RANGE.