




SSC8036GQ4

N-Channel Enhancement Mode MOSFET

➤ Features


VDS	VGS	RDSON Typ.	ID
30V	±20V	14mR@10V	18A
		20mR@4V5	

➤ Pin configuration



➤ Description

This device uses advanced trench technology to provide excellent RDSON and low gate charge. This device is suitable for use as a load switch or in PWM applications.




Bottom View

➤ Applications

- Load Switch
- NB/PC
- DCDC conversion

➤ Ordering Information

Device	Package	Shipping
SSC8036GQ4	DFN3x3	5000/Reel



(Y: year/W: week)

Marking

**➤ Absolute Maximum Ratings**($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Ratings	Unit	
V_{DSS}	Drain-to-Source Voltage	30	V	
V_{GSS}	Gate-to-Source Voltage	± 20	V	
I_D	Continuous Drain Current	TC=25°C	18	A
		TC=100°C	13	A
I_{DM}	Pulsed Drain Current ^b	102	A	
I_{DSM}	Continuous Drain Current ^a	TA=25°C	8.6	A
		TA=70°C	5.8	A
P_D	Power Dissipation ^c	TC=25°C	24	W
		TC=100°C	9.5	W
P_{DSM}	Power Dissipation ^a	TA=25°C	3	W
		TA=70°C	2	W
E_{AS}	Avalanche Energy L=0.1mH	42	mJ	
T_J	Operation junction temperature	-55 to 150	°C	
T_{STG}	Storage temperature range	-55 to 150	°C	

➤ Thermal Resistance Ratings($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Typical	Maximum	Unit
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance ^a		45	°C/W
$R_{\theta JC}$	Junction-to-Case Thermal Resistance		5.5	

Note:

- The value of $R_{\theta JA}$ is measured with the device mounted on 1 in² FR-4 board with 2oz.copper, in a still air environment with $T_A=25^{\circ}\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.
- Repetitive rating, pulse width limited by junction temperature.
- The power dissipation P_D is based on $T_J(\text{MAX})=150^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heat sinking is used.




➤ **Electronics Characteristics**($T_A=25^{\circ}\text{C}$ unless otherwise noted)


Symbol	Parameter	Test Conditions	Min	Typ.	Max	Unit
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	30			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	1		3	V
$R_{DS(on)}$	Drain-Source On- Resistance	$V_{GS}=10V, I_D=15A$		14	21	mR
		$V_{GS}=4.5V, I_D=12A$		20	36	
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=24V, V_{GS}=0V$			1	μA
I_{GSS}	Gate-Source leak current	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
G_{FS}	Transconductance	$V_{DS}=15V, I_D=12A$		16		S
V_{SD}	Forward Voltage	$V_{GS}=0V, I_S=1A$		0.8	1.5	V
C_{iss}	Input Capacitance	$V_{DS}=15V, V_{GS}=0V, f=1MHz$		550		pF
C_{oss}	Output Capacitance			180		
C_{rss}	Reverse Transfer Capacitance			95		
$T_{D(ON)}$	Turn-on delay time	$V_{GS}=10V,$ $V_{DS}=15V, R_L=2.3R, R_G=3R$		16		ns
T_r	Rise Time			32		
$T_{D(OFF)}$	Turn-off delay time			18		
T_f	Fall Time			55		
Q_g	Total Gate Charge	$V_{DS}=15V, V_{GS}=10V, I_{DS}=7A$		13		nC
Q_{gs}	Gate Source Charge			1.6		
Q_{gd}	Gate Drain Charge			2.4		




➤ **Typical Characteristics** ($T_A=25^\circ\text{C}$ unless otherwise noted)




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage




On-Resistance vs. Gate-to-Source Voltage




On-Resistance vs. Junction Temperature




Safe Operating Area, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Ambient

➤ Package Information


TOP VIEW



BOTTOM VIEW



SIDE VIEW

DFN3X3-8L

Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.70	0.75	0.80
A1	0.00	0.02	0.05
A2	0.20Ref		
D	2.90	3.00	3.10
E	2.90	3.00	3.10
D1	2.35	2.40	2.45
E1	1.65	1.70	1.75
b	0.25	0.30	0.35
e	0.65BSC		
L	0.37	0.42	0.47



DISCLAIMER

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.